Cablecraft

Technical Data.



Nylon insulated copper tube terminals.

Key features.

• Made from electrolytic copper, rolled, tin plated and brazed

• These nylon insulated terminals create a secure and reliable, electrical and mechanical connection

Specification.

Material:
Tin-plated copper

Insulation sleeve:
Nylon

Service temperature range:
Heat resistant up to 650˚C

Part number	Conductor size mm²	Hole Ø (mm)	Øi	C1 (mm)	C2 (mm)	L	W	Pack quantity
CNCT10-4	10	4	4.6	5.3	3.8	34.5	11	100
CNCT10-5		5	4.6	6.3	4.8	36.5	11	100
CNCT10-6		6	4.6	7.3	5.8	38.5	11	100
CNCT10-8		8	4.6	9.3	7.8	42.5	15	100
CNCT10-10		10	4.6	11.3	9.8	46.5	15	100
CNCT16-5	16	5	5.8	6.3	4.8	40	12	100
CNCT16-6		6	5.8	7.3	5.8	42	12	100
CNCT16-8		8	5.8	9.3	7.8	46	16	100
CNCT16-10		10	5.8	11.3	9.8	50	16	100
CNCT25-8	25	8	7	9.3	7.8	49.5	18	100
CNCT25-10		10	7	11.3	9.8	53.5	18	100
CNCT35-6	35	6	8.9	7.3	5.8	50.5	17	100
CNCT35-8		8	8.9	9.3	7.8	54.5	17	100
CNCT35-10		10	8.9	11.3	9.8	58.5	18	100
CNCT35-12		12	8.9	13.8	11.3	62.5	19	100
CNCT50-6	50	6	10	7.3	5.8	57	19	100
CNCT50-8		8	10	9.3	7.8	61	19	100
CNCT50-10		10	10	11.3	9.8	65	19	100
CNCT50-12		12	10	13.8	11.3	69	22	100
CNCT70-12	70	12	11.3	13.8	11.3	75	22	100
CNCT70-16		16	11.3	17.3	14.8	82	26	100
CNCT95-12	95	12	13.5	13.8	11.3	79.5	26	100
CNCT95-14		14	13.5	15.3	13.8	83.5	26	100
CNCT120-12	120	12	17	16	14	98	31	100
CNCT120-16		16	17	16	15	98	31	100

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Cablecraft part of Shoal Group Limited
Shoal Group Limited | Company registration number 12772850
Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX