Cablecraft

Technical Data.



Brass nickel plated cable glands - PG thread.

Key features.

- Suitable for high demands, offering excellent strain relief
- They offer high quality and total reliability
- Suitable for use in plant and automation technologies where exceptional and safe functioning and required
- EPN710/PG locknuts are sold separately

Specification.

Material:
Brass, nickel plated

Sealing ring:
Neoprene

Protection class:
IP 68

Temperature range:
-40˚C to +100˚C

Clamping insert:
Polyamide 6

O ring:
NBR

Part number	Thread size	TD (hole size mm)	TL (length of thread)	Cable range (min-max)	SW cap (mm)	SW body (mm)	D (mm)	H (mm)	Pack quantity
EPN 700/PG7	PG 7	12.5	6.0	3.0 - 6.5	14	14	15.5	24.0	1
EPN 700/PG9	PG 9	15.2	6.0	4.0 - 8.0	17	17	18.9	25.5	1
EPN 700/PG11	PG 11	18.6	6.0	5.0 - 10.0	20	20	22.0	28.0	1
EPN 700 PG13.5	PG 13.5	20.4	6.5	6.0 - 12.0	22	22	24.5	26.5	1
EPN 700/PG16	PG 16	22.5	6.5	10.0 - 14.0	24	24	26.5	30.0	1
EPN 700/PG21	PG 21	28.3	7.2	13.0 - 18.0	30	30	33.0	35.0	1
EPN 700/PG29	PG 29	37.0	8.0	18.0 - 25.0	40	40	44.5	40.5	1
EPN 700/PG36	PG 36	47.0	9.0	22.0 - 32.0	50	50	55.5	50.0	1
EPN 700/PG42	PG 42	54.0	12.0	30.0 - 38.0	58	58	64.0	51.0	1

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297