SolderSleeve terminators insulate, strain relieve and protect terminations from environmental damage in a wide range of applications at maximum operating temperatures of between 125˚C to 200˚C. They consist of a heat-shrinkable sleeve and a pre-measured, fluxed solder band. When heated the tubing shrinks and the solder melts creating reliable insulated terminations for even greater convenience.

The heatshrink tube and adhesive rings provide a seal resistant to water and other contaminants. The translucent heat shrink allows for visual inspection of the connection.

SPECIFICATION:

COLOUR OPTIONS: White, Red, Blue, Yellow

OPERATING TEMPERATURE: -125˚C to +200˚C

PART NUMBERS:

PART NO.	COLOUR	WIRE RANGE AWG	FOR SIZE MM²	PACK QTY
CSSBC1	White	38-28 AWG	0.1 - 0.5	10
CSSBC2	Red	22-18 AWG	0.5 - 1.5	25
CSSBC3	Blue	16-14 AWG	1.5 - 2.5	25
CSSBC4	Yellow	12-10 AWG	3.2 - 6.0	10

CABLECRAFT
creative wiring solutions

betaduct CABLECRAFT COMPANY
nqa ISO 9001 Registered UKAS QUALITY MANAGEMENT 015 CERTIFICATE NO. 9277
Link-up Registered I.D. 22645
INVESTORS IN PEOPLE
CTT CABLECRAFT COMPANY

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk
VAT NO. GB 639 920 900 • **CO. REG. NO.** 2478297