DESCRIPTION:

Our range of insulated tabs and receptacles are suitable for wires from 0.5mm² to 6.0mm². All types have a copper reinforcement sleeve and are made from copper-alloy, electro tinned. They feature high mechanical and dielectric resistant insulation, with heat resistant up to +75˚C.



SPECIFICATION:

PVC:

MATERIAL: Electro-tin plated copper
INSULATION: Polyvinyl Chloride
APPROVALS: RoHS compliant
MAX TEMPERATURE: 75°C
MAX VOLTAGE: 300V

NYLON:

MATERIAL: Electro-tin plated copper
INSULATION: Nylon
APPROVALS: RoHS compliant
MAX TEMPERATURE: 105°C
MAX VOLTAGE: 300V

PART NUMBERS:

COLOUR/WIRE Ø mm²	PART NO.		Max. elect. rating (A)	DIMENSIONS (mm)						
	PVC	NYLON		B	L	F	E	D	D1	PACK QTY
0.5-1.5 RED	CIAB1M	CNIAB1M	10	4.0	23.0	8.5	10.0	4.3	1.7	100
1.5-2.5 BLUE	CIAB2M	CNIAB2M	15	4.0	23.0	8.5	10.0	5.0	2.3	100
	CIAB2M5	CNIAB2M5	15	5.0	23.0	8.5	10.0	5.0	2.3	100
4-6 YELLOW	CIAB3M	CNIAB3M	24	5.0	25.0	8.5	13.0	6.5	3.4	100

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk