Cablecraft

Technical Data.



Tin plated copper sleeving braid.

Key features.

• Optimum screening performance is obtained using copper wire braid that can also be used for earth continuity purposes

• Used to provide sensitive cables with an EMC screen to shield them against electromagnetic, electrostatic and radio frequency interference

Specification.

Material:
High grade tin-plated copper

Service temperature range:
-65°C to +150°C

Approvals:
Conforms to BS EN13602:2008 and ASTM B33. RoHS 2 compliant

Part number	Former O/D mm	Min. optical coverage	Wire Ø mm	Usable Ø min (mm)	Usable Ø max (mm)	Pack quantity
CMBS3.0	3.0	90%	0.13	2.0	3.5	100
CMBS4.0	4.0	90%	0.13	3.0	5.0	100
CMBS5.0	5.0	90%	0.13	4.0	6.0	100
CMBS6.0	6.0	90%	0.13	5.0	7.0	100
CMBS10.0	10.0	90%	0.16	7.0	12.0	50
CMBS12.5	12.5	90%	0.16	11.0	13.0	50
CMBS15.0	15.0	90%	0.20	13.0	18.0	50
CMBS20.0	20.0	90%	0.13	17.0	23.0	50
CMBS25.0	25.0	90%	0.13	22.0	28.0	50
CMBS30.0	30.0	90%	0.16	27.0	36.0	50
CMBS 95 3.0	3.0	95%	0.10	2.5	5.0	100
CMBS 95 4.0	4.0	95%	0.13	3.5	7.5	100
CMBS 95 6.0	6.0	95%	0.13	4.5	9.5	100
CMBS 95 7.5	7.5	95%	0.13	7.0	14.0	100
CMBS 95 10.0	10.0	95%	0.13	8.0	22.0	100
CMBS 95 12.5	12.5	95%	0.13	11.0	24.0	100
CMBS 95 20.0	20.0	95%	0.13	16.0	38.0	100
CMBS 95 25.0	25.0	95%	0.13	22.0	38.0	50
CMBS 95 30.0	30.0	95%	0.16	27.0	40.0	50
CMBS 95 35.0	35.0	95%	0.16	30.0	50.0	50
CMBS 95 40.0	40.0	95%	0.20	35.0	60.0	50

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297