Cablecraft

Technical Data.








EMC 2 PG thread cable glands.

Key features.

• Consists of body plastic inlet, EMC spring and neoprene seal

• Combines several advantages in one product; it offers the same clamping range as with the normal brass gland



Specification.

Material:
Brass nickel plated

Protection class:
IP 68

Temperature range:
-40°C to +100°C

Clamping insert:
Polyamide 6

Sealing ring:
Neoprene

Part number	Thread size	TL (length of thread)	Cable range min-max Ø (mm)	Shield dia min-max Ø (mm)	SW cap (mm)	SW body (mm)	D (mm)	H (mm)	Pack quantity
EMC2-PG7	PG7	6.0	3.0 - 6.5	2.5 - 4.5	14	14	15.5	24.0	1
EMC2-PG9	PG9	6.0	4.0 - 8.0	3.5 - 6.0	17	17	18.9	25.5	1
EMC2-PG11	PG11	6.0	5.0 - 10.0	4.0 - 8.0	20	20	22.0	28.0	1
EMC2-PG13.5	PG13.5	6.5	6.0 - 12.0	5.0 - 10.0	22	22	24.5	26.5	1
EMC2-PG16	PG16	6.5	10.0 - 14.0	8.5 - 11.5	24	24	26.5	30.0	1
EMC2-PG21	PG21	7.2	13.0-18.0	11.0 - 14.0	30	30	33.0	35.0	1
EMC2-PG29	PG29	8.0	18.0 - 25.0	16.0 - 20.0	40	40	44.5	40.5	1
EMC2-PG36	PG36	9.0	22.0 - 32.0	20.0 - 27.0	50	50	55.5	50.0	1
EMC2-PG42	PG42	12.0	30.0 - 38.0	28.0 - 34.0	58	58	64.0	51.0	1
EMC2-PG48	PG48	14.0	34.0 - 44.0	31.0 - 40.0	64	64	70.0	55.0	1

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297