DESCRIPTION:

Our nylon insulated halogen-free miniature ring terminals are suitable for wire size 0.1-0.5 mm². They are electro-tin plated for excellent conductivity and resistance to corrosion.

APPLICATIONS:

Our Halogen-Free terminals create a secure and reliable, electrical and mechanical connection.

SPECIFICATION:

MATERIAL: 316 Stainless Steel

SERVICE TEMPERATURE RANGE: Heat resistant up 1700°C

VOLTAGE: 3.3Kv

STANDARDS: RoHS 2 compliant



PART NUMBERS:

				DIMENSIONS (mm)							
COLOUR/ WIRE Ø MM²	**MAX. ELECT RATING (A)**	**PART NUMBER**	**INSULATION TYPE**	**D2**	**B**	**L**	**F**	**E**	**D**	**D1**	**PACK QTY**
0.1-0.5 YELLOW	9	CNIR0.1-2	Nylon	2.2	5.0	16.5	14.0	8.0	2.4	1.0	100
	9	CNIR0.1-2.5	Nylon	2.7	5.0	16.5	14.0	8.0	2.4	1.0	100
	9	CNIR0.1-3	Nylon	3.2	5.0	16.5	14.0	8.0	2.4	1.0	100
	9	CNIR0.1-3.5	Nylon	3.7	6.0	19.0	16.0	8.0	2.4	1.0	100
	9	CNIR0.1-4	Nylon	4.3	6.5	19.2	16.0	8.0	2.4	1.0	100
	9	CNIR0.1-5	Nylon	5.3	8.0	20.0	16.0	8.0	2.4	1.0	100

CABLECRAFT™
creative wiring solutions

betaduct
CABLECRAFT COMPANY

CERTIFICATE NO. 9277

I.D. 22645

INVESTORS IN PEOPLE

CABLECRAFT COMPANY

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk
VAT NO. GB 639 920 900 • **CO. REG. NO.** 2478297

FILE NO. 2.73
ISSUE NO. 02