DESCRIPTION:

Single/double sided 3:1 heat-shrinkable polyolefin sleeves fit snugly around wires for maximum insulation and permanent identification. The material does not smudge or fade when printed and is self-extinguishing.

APPLICATIONS:

Ideal for panel identification, wire and cable marking.

SPECIFICATION:

MATERIAL: PermaSleeve heatshrink polyolefin sleeves, 3:1 shrink ratio, self-extinguishing.

SERVICE TEMPERATURE RANGE: -55˚C to +130˚C

AVAILABLE LABEL COLOURS:

WHITE WT	**BLACK** BK	**BLUE** BL	**GREY** GY
GREEN GR	**RED** RD	**YELLOW** YL	**ORANGE** OR
BROWN BR	**PINK** PK	**VIOLET** VT	

For example, when ordering a colour, insert the code in place of WT (White) on your part number. Minimum quantity orders may apply. Please contact us for more information.

PART NUMBERS:

PART NUMBER	LABEL HEIGHT/MAX WIRE DIA. (mm)	WIDTH (mm)	SHRUNK DIA. (mm)	TRI-RATE CABLE SIZE (mm²)
PP-RPS22-18	3.2	25mm & 50mm	1.07	0.50-1mm²
PP-RPS18-12	4.8	25mm & 50mm	1.57	1-4mm²
PP-RPS16-10	6.4	25mm & 50mm	2.11	4-6mm²
PP-RPS8-4	9.5	25mm & 50mm	3.18	6-16mm²
PP-RPS10-2	12.7	25mm & 50mm	4.22	16-35mm²
PP-RPS6-250	19	25mm & 50mm	6.35	25-70mm²
PP-RPS1-400	25.4	25mm & 50mm	8.46	35-120mm²

1. Contact us to discuss options and obtain part numbers **Tel: 01582 606 033**
2. Complete an Excel spreadsheet with your order requirements and quantities, send to: **preprint@cablecraft.co.uk**

CABLECRAFT™
creative wiring solutions

betaduct CABLECRAFT COMPANY

nqa ISO 9001 Registered UKAS QUALITY MANAGEMENT 015
CERTIFICATE NO. 9277

Link-up Registered
I.D. 22645

INVESTORS IN PEOPLE

CTT CABLECRAFT COMPANY

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk
VAT NO. GB 639 920 900 • **CO. REG. NO.** 2478297

FILE NO. 1.8
ISSUE NO. 02