



Uninsulated cord end terminals.

Key features.

- Manufactured from tin plated electrolytic copper
- Covers cable sizes from 0.5mm² to 150mm²
- Designed to terminate the end of a cable, prior to fitting into screw type terminal blocks or connectors

Specification.

Material:
Tin Plated Electrolytic Copper

Heat resistance:
Up to 125 °C

Standards:
DIN 46228 part 1. RoHS 2 compliant

Part no.	Size (mm ²)	L1 (mm)	D1 (mm)	S (mm)	Pack quantity
CUT0.14-7	0.14	7	0.65	0.15	1000
CUT0.25-7	0.25	7	0.75	0.15	1000
CUT0.34-7	0.34	7	0.85	0.15	1000
CUT0.5-6.0	0.50	6	1.0	0.15	1000
CUT0.5-10	0.50	10	1.0	0.15	1000
CUT0.75-6	0.75	6	1.2	0.15	1000
CUT0.75-10	0.75	10	1.2	0.15	1000
CUT1.0-6	1.00	6	1.4	0.15	1000
CUT1.0-10	1.00	10	1.4	0.15	1000
CUT1.5-7	1.50	7	1.7	0.15	1000
CUT1.5-10	1.50	10	1.7	0.15	1000
CUT2.5-7	2.50	7	2.2	0.15	1000
CUT2.5-10	2.50	10	2.2	0.15	1000
CUT4.0-9	4.00	9	2.8	0.20	1000
CUT4.0-12	4.00	12	2.8	0.20	1000
CUT6.0-15	6.00	15	3.5	0.20	100

Part no.	Size (mm ²)	L1 (mm)	D1 (mm)	S (mm)	Pack quantity
CUT6.0-18	6.00	18	3.5	0.20	100
CUT10.0-15	10.00	15	4.5	0.20	100
CUT10.0-18	10.00	18	4.5	0.20	100
CUT16.0-15	16.00	15	5.8	0.20	100
CUT16.0-18	16.00	18	5.8	0.20	100
CUT25-15	25.00	15	7.3	0.20	100
CUT25-18	25.00	18	7.3	0.20	100
CUT35-18	35.00	18	8.3	0.20	100
CUT35-25	35.00	25	8.3	0.20	100
CUT50	50.00	25	10.3	0.30	50
CUT70	70.00	25	12.5	0.35	50
CUT95	95.00	30	14.5	0.35	50
CUT120	120.00	34	16.5	0.45	10
CUT150	150.00	38	18.5	0.50	10