Cablecraft

Technical Data.



Nylon locknuts - PG thread.

Key features.

- They provide the highest degrees of functionality and safety
- The sealing nut is designed to provide a perfect grip and effortless spanner-tight seal

Part number	Thread size	Depth (mm)	SW (mm)	D (mm)	Pack quantity
EPN 350/PG7	PG 7	5.0	19	20.9	1
EPN 350/PG9	PG 9	5.0	22	23.9	1
EPN 350/PG11	PG 11	5.0	24	25.9	1
EPN 350/PG13.5	PG 13.5	6.0	27	28.9	1
EPN 350/PG16	PG 16	6.0	30	32.9	1
EPN 350/PG21	PG 21	7.0	36	38.8	1
EPN 350/PG29	PG 29	7.0	46	49.8	1
EPN 350/PG36	PG 36	8.0	60	65.7	1
EPN 350/PG42	PG 42	8.0	65	72.7	1
EPN 350/PG48	PG 48	8.0	70	77.7	1

Specification.

Material:
PA 6 GF 30 (Polyamide 6, 30% glass fiber reinforced)

Colour options:
Black, blue, light grey, dark grey, red, white

Flammability:
HB according to UL94

Operating temperature:
Permanent
-20°C to +100°C

Intermittent
-30°C to +150°C

Thread type:
Metric EN 60423
PG DIN 40430

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297