Cablecraft

Technical Data.







Stainless steel cable glands - metric thread.

Key features.

- IP68 rated offering protection against prolonged immersion under water
- Suitable for most demanding applications, offering excellent strain relief

Approvals	Certificate Number	Standards
DVE	40040034	DIN EN 62444
UL	E199260	UL514B CSA22.2 No 18.3-12 CSA22.2 No 94.2-1S
TYPE 4x		UL50E
DNV·GL	TAE00003WY	EN62444

Specification.

Material:
Stainless steel grade 316

Flammability:
V2 according to UL94

IP rating:
IP68

Operating temperature:
Permanent
-20˚C to +100˚C

Intermittent
-40˚C to +150˚C

Thread type:
Metric EN 60423

Part number	Thread size	TL (thread length)	Cable range min-max Ø (mm)	SW cap mm	SW body mm	D (mm)	H (mm)	Pack quantity
CSSG-M12	M12 x 1.5	6.0	3.0 - 6.5	14	14	15.5	24.0	1
CSSG-M16	M16 x 1.5	7.0	4.0 - 8.0	17	19	21.0	25.5	1
CSSG-M20	M20 x 1.5	8.0	6.0 - 12.0	22	22	24.5	26.5	1
CSSG-M25	M25 x 1.5	8.0	10.0 - 14.0	24	27	30.0	30.0	1
CSSG-M32	M32 x 1.5	9.0	13.0 - 18.0	30	36	39.8	35.0	1
CSSG-M40	M40 x 1.5	9.0	18.0 - 25.0	41	46	51.4	40.5	1
CSSG-M50	M50 x 1.5	9.0	22.0 - 32.0	50	55	61.0	50.0	1
CSSG-M63	M63 x 1.5	14.0	34.0 - 44.0	65	70	77.0	55.0	1

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297