Cablecraft

Technical Data.

Outdoor High Temperature Cable Ties.

A range of multi-toothed ratchet cable ties for strong locking, with high tensile strength. Excellent UV resistance suitable for outdoor use. Due to the properties of this product , it is ideal for high temperature applications such as railway, offshore and automotive industries.

HF Halogen Free

HT High Temperature

Part number	Width (mm)	Length (mm)	Max. bundle dia. (mm)	Min. Tensile Strength daN	Pack Qty
1790	3.5	140	32	13	100
1791		200	51	13	100
1792		280	75	13	100
1793		370	102	13	100
1724	4.6	200	51	22	100
1734		300	80	22	100
1744		380	110	22	100
1794	7.5	240	63	54	100
1795		280	82	54	100
1796		365	106	54	100
1797	9.0	550	155	79	100
1798		780	230	79	100

Specification.

Colour Options:
Black

Material:
Heat Resistant Nylon 6.6

Operating temperature:
-40˚C to +125˚C

Flame Resistance:
V2 UL94

Density:
1,140kg/m^3

Tensile Strength At Break:
60MPa

Ultimate Elongation:
20%

Tensile Modulus:
3200

Dielectric Strength:
27KV/mm

Charpy Notched Impact Strength:
5.0kJ/m^2

Standards:
UL: E160935

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297