Cablecraft

Technical Data.

Limited fire hazard cable ties.

Key features.

- Made from a self-extinguishing, V0:UL 94 halogen-free, fire proof material
- The multi-toothed ratchet cable ties enable strong locking and a high tensile strength
- Adapted for fixing beams and flexible cables
- Their inside serrations ensure efficient maintenance of cables
- Ideal for use in both demanding environments and general applications where limited fire hazard properties are required, such as public buildings, factories, offshore, railway stations and the underground

LFH Low Fire Hazard · RA Rail Approved · HF Halogen Free · UNDERGROUND

Part number	Colour	Length (mm)	Width (mm)	Max. bundle dia. mm	Min. tensile strength Kg	Pack quantity
1780-B	Black	100	2.5	23	3.25	100
1781-B	Black	145	3.5	32	6.6	100
1782-B	Black	210	3.5	51	6.6	100
1783-B	Black	300	4.6	75	6.6	100
1784-B	Black	380	4.5	100	7	100
1787-B	Black	375	7.5	106	10.3	100
1780	White	100	2.5	23	3.25	100
1781	White	145	3.5	32	6.6	100
1782	White	210	3.5	51	6.6	100
1783	White	300	4.6	75	6.6	100
1784	White	380	4.5	100	7	100
1786	White	300	7.5	82	8.3	100
1787	White	375	7.5	106	10.3	100

Specification.

Material:
Polyamide 6, halogen free

Colour options:
Black or white

Operating temperature:
-40˚C to +100˚C

Density:
1,160kg/m3

Ultimate elongation:
5%

Tensile strength at yield:
80MPa

Flame resistance:
V0 UL94/E44716

Dielectric strength:
34kV/mm

Melting point:
+220˚C

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297