



## TE Connectivity DR25 heat shrink tubing - Thin Wall.

### Key features.

- Made from a flexible radiation cross-linked elastomeric material specially formulated for optimum resistance to fluids at high temperature and long term exposure to heat
- It offers excellent protection & insulation
- Suitable for protecting cable and high performance wiring harnesses against aviation fuels, diesel fuel, hydraulic fluids and lubricating oils
- 2:1 shrink ratio
- Excellent chemical and solvent resistance, abrasion & mechanical protection

**Please Note: This heat shrink tubing is sold by the metre**



### Specification.

**Material:**  
Flexible cross-linked elastomeric

**Operating temperature:**  
-75°C to +150°C

**Shrink temperature:**  
175°C

**Specifications:**  
MIL-DTL-23053/16 (except 1/8 & 3/16); Def Stan 59-97 Issue 3 Type 6B; VG 95343 Part 5 Type D, BS 3G-198 Part 3 10A, RK-8006 & RT-1116

Part number	Dia. size (mm)	Fully recovered inside dia. (mm)	Recovered wall thickness (mm)*	Min quantity (m)
DR-25-TW-3/32-O-SP	3.2	1.6	0.51 ± 0.08	1
DR-25-TW-1/8-O-SP	4.8	2.4	0.51 ± 0.10	1
DR-25-TW-3/16-O-SP	6.4	3.2	0.64 ± 0.10	1
DR-25-TW-3/4-O-SP	9.53	4.8	0.64 ± 0.10	1
DR-25-TW-1-O-SP	12.7	6.4	0.64 ± 0.10	1
DR-25-TW-1-1/4-O-SP	19.0	9.5	0.76 ± 0.12	1
DR-25-TW-1-1/2-O-SP	25.4	12.7	0.89 ± 0.16	1

\*Wall thickness will be less if tubing recovery is restricted during shrinkage