




DESCRIPTION:

Y distributor connectors are specially designed to join three conduits of different nominal diameter when small bending radiuses have to be avoided. In accordance with EN 60204.

SPECIFICATION:

MATERIAL: Polyamide (PA 6) - Free of Halogen, Phosphorus and Cadmium.

IP RATING: IP 66 Protection. IP68 with ORJ O-Rings

SERVICE TEMPERATURE RANGE: -40°C to +105°C

STANDARDS: EN 60204 (Safety of Machinery).

APPROVALS: UL Approved - E225913



PART NUMBERS:

PART NO. BLACK	PART NO. GREY	CONDUIT SIZE (mm)	DIMENSIONS (mm)									PK QTY
			A	B	C1	C2	D	E	F	H	J	
YKD-201212B	YKD-201212G	20+2x12	89	47	18	14	34	37	5	9	24	1
YKD-252020B	YKD-252020G	25+2x20	106	58	24	18	45	44	6	12	28	1
YKD-322525B	YKD-322525G	32+2x25	118	74	30	24	52	45	6	15	35	1
YKD-403232B	YKD-403232G	40+2x32	141	89	38	30	60	52	6	19	41	1
YKD-504040B	YKD-504040G	50+2x40	153	106	49	38	76	54	7	25	50	1