Technical Data.

Betaflex 4 PVC coated galvanised conduit.

Key features.

• It has good mechanical stability and flexibility

• For commercial applications for example, offices, factories and under floor wiring

• Designed for use in general wiring conditions and where light mechanical stress may occur

Part number	Conduit size (mm)	Outside dia. (mm)	Inside dia. (mm)	Reel quantity (m)
GSP20 (LENGTH)	20	21	17	10 or 30
GSP25 (LENGTH)	25	27	22	10 or 30
GSP32 (LENGTH)	32	34	28.1	10 or 30
GSP50 (LENGTH)	50	55	48	10 or 30
GSP63 (LENGTH)	63	65	57	10 or 30
GSP75 (LENGTH)	75	77	70	10 or 30
GSP100 (LENGTH)	100	102	93	10 or 30

Specification.

Material:
Galvanised steel, PVC coated

Service temperature range:
-20°C to +80°C

Crush resistance:
To 1500N

Standards:
EN 50086 galvanised to DIN 53210

IP rating:
IP 67

01582 606033 | **sales@cablecraft.co.uk** | **cablecraft.co.uk**
Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297